

# Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/01/2016 Supersedes: 04/21/2009 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Seam Glue DC
Product form : Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Purchase Green MDC 5160 Richton St. Unit D Montclair. CA 91763

Information telephone number: 844-TURF-4441.4. Emergency telephone number

Emergency number : 844-TURF-444

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Acute Tox. 4 (Inhalation:dust,mist) H332 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Resp. Sens. 1 H334 Skin Sens. 1 H317 STOT SE 3 H335 STOT RE 1 H372

#### 2.2. Label elements

### **GHS-US labelling**

Hazard pictograms (GHS-US)





Signal word (GHS-US) : Danger

Hazard statements (GHS-US)

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
 Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause respiratory irritation. Causes damage to organs (respiratory system) through prolonged or repeated exposure

Precautionary statements (GHS-US)

Do not breathe mist, spray, vapours. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. [In case of inadequate ventilation] wear respiratory protection. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell. Specific treatment (see first aid instructions on this label). If skin irritation or rash occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a doctor, a poison center. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substance

Not applicable

#### 3.2. Mixture

01/01/2016 Seam Glue DC Page 1

# Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%
Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]-	(CAS No) 5873-54-1	10 - 25
4-4'-Methylenediphenyl diisocyanate	(CAS No) 101-68-8	10 - 20
Benzene, 1,1'-methylenebis[2-isocyanato-	(CAS No) 2536-05-2	0 - 2

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the

doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an

unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial

respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at

least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact

lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get

medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison

control center or medical professional. Get medical attention immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. May cause an allergic

skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Causes damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Dry chemical. Carbon dioxide.

Unsuitable extinguishing media : None known.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Product is not flammable.

Explosion hazard : No data available.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill should be handled by trained clean-up crews properly equipped with respiratory

equipment and full chemical protective gear (see Section 8). Evacuate area. Ventilate area.

Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air

respirator, in case of emergency.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

01/01/2016 Seam Glue DC 2/6

# Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.3. Methods and material for containment and cleaning up

For containment

: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.

Methods for cleaning up

: Soak up with inert material. Sweep up material and place in an appropriate chemical waste container for disposal. Do not discharge to sewers or waterways. Apply neutralizing solution over spill area & absorbent. Place into containers (closed but not sealed) for waste disposal. Apply neutralizing solution to the absorbed material in the waste container to ensure adequate decontamination. Monitor the drum frequently for the next 48-72 hours in case

overpressurization results from continued reaction and while carbon dioxide escapes. Dispose

of material in compliance with local, state, and federal regulations.

#### 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Use appropriate personal protection equipment (PPE). Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of reach of children. Keep container tightly closed. Keep in properly labeled containers. Do not reseal if contamination is suspected. Store in a cool dry place away from heat, flame and incompatible materials.

Incompatible materials : Moisture.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]- (5873-54-1)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	
4-4'-Methylenediphenyl diisocyanate (101-68-8)		
ACGIH TWA (ppm)	0.005 ppm (listed under Methylene bisphenyl isocyanate (MDI))	
OSHA PEL (Ceiling) (mg/m³)	0.2 mg/m³	
OSHA PEL (Ceiling) (ppm)	0.02 ppm	
Benzene, 1,1'-methylenebis[2-isocyanato- (2536-05-2)		
Remark (ACGIH)	OELs not established	
Remark (OSHA)	OELs not established	

## 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

 Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

01/01/2016 Seam Glue DC 3/6

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Green.
Odor : Mild odor.

Odor Threshold : No data available : No data available рΗ Relative evaporation rate (butylacetate=1) No data available : No data available Melting point Freezing point : No data available Boiling point : No data available > 204.4 °C (>400 °F) Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C : Heavier than air Relative density : 1.05 (H2O=1) Solubility Water: Reacts Log Pow No data available Log Kow : No data available Viscosity, kinematic : No data available

Explosive limits9.2. Other informationNo additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Viscosity, dynamic Explosive properties

Oxidising properties

No dangerous reactions known under normal conditions of use.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# 10.4. Conditions to avoid

Hazardous polymerization may occur if in contact with moisture or other materials which react with isocyanates. Hazardous polymerization may occur at temperatures over 204 °C (400 °F.).

#### 10.5. Incompatible materials

Water, amines, strong bases, alcohols. Will cause some corrosion to copper alloys and aluminum.

# 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2). Nitrogen oxides.

### **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust/mist: Harmful if inhaled. Inhalation:dust/mist: Not classified.

: No data available

: No data available

No data availableNo data available

Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]- (5873-54-1)		
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	
4-4'-Methylenediphenyl diisocyanate (101-68-8)		
LD50 oral rat	31600 mg/kg	
LC50 inhalation rat (mg/l)	369 mg/m³ 4 h	

01/01/2016 Seam Glue DC 4/6

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-4'-Methylenediphenyl diisocyanate (101-68-8)		
ATE CLP (gases)	4500.000 ppmv/4h	
ATE CLP (vapours)	11.000 mg/l/4h	
ATE CLP (dust,mist)	1.500 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

 $: \ \ \, \text{Causes damage to organs (respiratory system) through prolonged or repeated exposure.} \\$ 

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

Chronic symptoms : Causes damage to organs through prolonged or repeated exposure.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

No additional information available

# 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities.

No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose of in accordance with local/national regulations. Do not allow the product to be

released into the environment. Do not re-use empty containers.

# **SECTION 14: Transport information**

In accordance with DOT Not hazardous for transport

**Additional information** 

Other information : No supplementary information available.

## Transport by sea

No additional information available

#### Air transport

No additional information available

## **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

## Seam Glue DC

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

01/01/2016 Seam Glue DC 5/6

# Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Seam Glue DC	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Delayed (chronic) health hazard

## 15.2. International regulations

No additional information available.

### 15.3. US State regulations

This product does not contain any substances known to the state of California to cause cancer and/or reproductive

## 4-4'-Methylenediphenyl diisocyanate (101-68-8)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## **SECTION 16: Other information**

Indication of changes : Revision 1.0: New SDS Created

Revision date : 01/01/2016 Other information : Author: SJR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was


given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated

temperatures and pressures or may react with water with

some release of energy, but not violently.



# **HMIS III Rating**

Health: 3\*Flammability: 1Physical: 1Personal Protection:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

01/01/2016 Seam Glue DC 6/6