

Safety Data Sheet

ULTRABOND LANDSCAPE TURF CG (NA)

Safety Data Sheet dated: 09/24/2025 - version 10

Date of first edition: 10/28/2019



1: Identification

Product identifier

Mixture identification:

Trade name: ULTRABOND LANDSCAPE TURF CG (NA)

Trade code: 9023332

Recommended use and restrictions on use

Recommended use: Polyurethane-based adhesive

Restrictions on use: Not available

Supplier's details

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue

H7L 3J5 - Laval - QC - CAN

Phone: 1-450-662-1212

Responsible: RDProductSafety@mapei.com

Emergency phone number

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. Hazard identification



Classification of the product

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Respiratory Sensitization, Category 1

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sensitization, Category 1

May cause an allergic skin reaction.

Specific target organ toxicity following repeated exposure, Category 2

May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Carcinogenicity, Category 2

Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P280	Wear protective gloves/clothing and eye/face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a doctor.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. Composition/information on ingredients

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of WHMIS 2015 (HPR and its amendments) and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
≥10 - <15 %	4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	CAS:101-68-8 EC:202-966-0 Index:615-005-00-9	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351
≥1 - <2.5 %	4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	CAS:4083-64-1 EC:223-810-8 Index:615-012-00-7	Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334
≥1 - <2.5 %	2,2-dimorpholinodiethylether; Bis(2-morpholinoethyl) Ether	CAS:6425-39-4 EC:229-194-7	Eye Irrit. 2A, H319
≥0.1 - <0.2 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350

The actual concentration of the components listed above is withheld as a trade secret.

Declared percentages are expressed in w/w

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.
- If skin irritation or rash occurs: Get medical advice/attention.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.
- Remove contact lenses, if present and easy to do. Continue rinsing.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Wash skin thoroughly after handling.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.
Storage temperature: Not available

8. Exposure controls/personal protection
Control parameters

Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- CAS: 101-68-8	ACGIH		Long Term: 0,005 ppm Resp sens
	MAK	GERMANY	Long Term: 0,05 mg/m3
	ACGIH		Long Term: 0,005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0,2 mg/m3 - 0,02 ppm
	MAK	AUSTRIA	Long Term: 0,05 mg/m3 - 0,005 ppm; Short Term: 0,1 mg/m3 - 0,01 ppm
	ACGIH		Long Term: 0,005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
silica sand; quartz CAS: 14808-60-7	OSHA		Short Term: Ceiling - 0,2 mg/m3 - 0,02 ppm
	EU		Long Term: 0,006 mg/m3; Short Term: 0,012 mg/m3 Skin; Dermal and respiratory sensitisation
	ACGIH		Long Term: 0,025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0,15 mg/m3
	ACGIH		Long Term: 0,025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0,15 mg/m3
	EU		Long Term: 0,1 mg/m3 Behaviour Binding

Predicted No Effect Concentration (PNEC) values

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- CAS: 101-68-8	Exposure Route: Fresh Water; PNEC Limit: 1 mg/l
	Exposure Route: Marine water; PNEC Limit: 0,1 mg/l
	Exposure Route: Soil; PNEC Limit: 1 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l
2,2-dimorpholinodiethylether; Bis(2-morpholinoethyl) Ether CAS: 6425-39-4	Exposure Route: Intermittent release; PNEC Limit: 10 mg/l
	Exposure Route: Fresh Water; PNEC Limit: 0,1 mg/l
	Exposure Route: Marine water; PNEC Limit: 0,01 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 8,2 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 0,82 mg/kg
	Exposure Route: Soil; PNEC Limit: 1,58 mg/kg

Derived No Effect Level (DNEL) values

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- CAS: 101-68-8	Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects Worker Industry: 50 mg/kg
	Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects Worker Industry: 0,1 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Industry: 0,1 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 0,05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Industry: 0,05 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Consumer: 25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Consumer: 0,05 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 20 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Consumer: 0,05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 0,025 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Consumer: 0,025 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects
Worker Industry: 28,7 mg/cm2; Consumer: 17,2 mg/cm2

2,2-dimorpholinodiethylether;
Bis(2-morpholinoethyl)
Ether
CAS: 6425-39-4

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Industry: 7,28 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Industry: 1 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Consumer: 1,8 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Consumer: 0,5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 0,5 mg/kg

Appropriate engineering controls

Not available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste green

Odour: mild

Odour threshold: Not Relevant
Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant
Flammability: Not Relevant
Upper/lower flammability or explosive limits: Not Relevant
Flash point: 94 °C (201 °F)
Auto-ignition temperature: Not Relevant
Decomposition temperature: Not Relevant
pH: Not Relevant
Viscosity: 115.00 mPA-s
Kinematic viscosity: > 20,5 mm2/sec (40 °C) mm2/s
Solubility in water: insoluble
Solubility in oil: partly soluble
Partition coefficient (n-octanol/water): Not Relevant
Vapour pressure: Not Relevant
Evaporation rate: Not Relevant
Relative density: 1.07 g/cm3
Vapour density: Not Relevant

Particle characteristics:

Particle size: No data available

Other information

Explosive properties: Not Relevant
Oxidizing properties: Not Relevant
Solid/gas flammability: Not Relevant
Substance Groups relevant properties: Not Relevant
Miscibility: Not Relevant
Fat Solubility: Not Relevant
Conductivity: Not Relevant

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Likely routes of exposure:

Skin contact, skin absorption, eye contact, inhalation and ingestion.

Toxicological Information of the Preparation

- | | |
|--------------------------------------|--|
| a) acute toxicity | Not classified
Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation | The product is classified: Skin irritation, Category 2(H315) |
| c) serious eye damage/irritation | The product is classified: Eye irritation, Category 2A(H319) |
| d) respiratory or skin sensitisation | The product is classified: Respiratory Sensitization, Category 1(H334), Skin Sensitization, Category 1(H317) |
| e) germ cell mutagenicity | Not classified
Based on available data, the classification criteria are not met |
| f) carcinogenicity | The product is classified: Carcinogenicity, Category 2(H351) |
| g) reproductive toxicity | Not classified
Based on available data, the classification criteria are not met |

h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: Specific target organ toxicity following repeated exposure, Category 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg	
	f) carcinogenicity	Carcinogenicity Inhalation Rat = 6, mg/m ³	2 y
	g) reproductive toxicity	NOAEL Inhalation Rat = 12, mg/m ³	20 d
4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	a) acute toxicity	LC50 Inhalation Rat > 640 ppm 1h	
		LD50 Oral Rat = 2234 mg/kg	
2,2-dimorpholinodiethylether; Bis(2-morpholinoethyl) Ether	a) acute toxicity	LD50 Skin Rabbit = 3038 mg/kg	
		LD50 Oral Rat = 2025 mg/kg	
		LD50 Oral Rat 300 mg/kg	
silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg	

Substance(s) listed on the IARC Monographs:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	Group 3
silica sand; quartz	Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	CAS: 101-68-8 - EINECS: 202-966-0 - INDEX: 615-005-00-9	a) Aquatic acute toxicity : LC50 Fish > 1000 mg/L 96
		a) Aquatic acute toxicity : EC50 Daphnia > 1000 mg/L 24

- b) Aquatic chronic toxicity : NOEC Daphnia > 10 mg/L - 21 d
- a) Aquatic acute toxicity : EC50 Algae > 1640 mg/L 72
- c) Bacteria toxicity : EC50 > 100 mg/L 3
- d) Terrestrial toxicity : NOEC > 1000 mg/kg - 14 d
- e) Plant toxicity : NOEC > 1000 mg/kg - 14 d

2,2-dimorpholinodiethylether;
Bis(2-morpholinoethyl) Ether

CAS: 6425-39-4
- EINECS: 229-194-7

- a) Aquatic acute toxicity : LC50 Fish > 2150 mg/L 96

- a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/L 48
- a) Aquatic acute toxicity : LC50 Fish Danio rerio > 2150 mg/L 96h ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

TDG-UN number: Not Applicable

ADR-UN number: Not Applicable

DOT-UN Number: Not Applicable

IATA-Un number: Not Applicable

IMDG-Un number: Not Applicable

UN proper shipping name

TDG-Shipping Name: Not Applicable

ADR-Shipping Name: Not Applicable

DOT-Proper Shipping Name: Not Applicable

IATA-Technical name: Not Applicable

IMDG-Technical name: Not Applicable

Transport hazard class(es)

TDG-Class: Not Applicable

ADR-Class: Not Applicable

DOT-Hazard Class: Not Applicable

IATA-Class: Not Applicable

IMDG-Class: Not Applicable

Packing group

TDG-Packing Group: Not Applicable
ADR-Packing Group: Not Applicable
DOT Packing Group: Not Applicable
IATA-Packing group: Not Applicable
IMDG-Packing group: Not Applicable

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs
Not Applicable

Special precautions in connection with transport or conveyance

TDG:

Not Applicable

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID) :

Not Applicable

Air (IATA) :

Not Applicable

Sea (IMDG) :

Not Applicable

15. Regulatory information**Canada - Federal regulations**

This Safety Data Sheet has been prepared according to the WHMIS Hazardous Products Regulations (SOR/2015-17 as amended by SOR/2022-272).

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

USA - Federal regulations**TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

TSCA listed substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- is listed in TSCA Section 8b Section 8a - PAIR Section 5

4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene is listed in TSCA Section 8b

2,2-dimorpholinodiethylether; Bis(2-morpholinoethyl) Ether is listed in TSCA Section 8b

silica sand; quartz is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act**Section 302 - Extremely Hazardous Substances:**

No substances listed

Section 304 - Hazardous substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

Section 313 - Toxic chemical list:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**Substance(s) listed under CERCLA:**

4,4'-methylenediphenyl diisocyanate; Reportable quantity: 5000 pounds
benzene, 1,1'-methylenebis[4-isocyanato-

CAA - Clean Air Act

CAA listed substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act**CWA listed substances:**

No substances listed

USA - State specific regulations**California Proposition 65****Substance(s) listed under California Proposition 65:**

silica sand; quartz Listed as carcinogen

Massachusetts Right to know**Substance(s) listed under Massachusetts Right to know:**

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-silica sand; quartz

Pennsylvania Right to know**Substance(s) listed under Pennsylvania Right to know:**

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-silica sand; quartz

New Jersey Right to know**Substance(s) listed under New Jersey Right to know:**

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-silica sand; quartz

16. Other information

Safety Data Sheet dated: 9/24/2025 - version 10

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.1/1	Resp. Sens. 1	Respiratory Sensitization, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
IMDG: International Maritime Code for Dangerous Goods.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
CLP: Classification, Labeling, Packaging.
EINECS: European Inventory of Existing Commercial Chemical Substances.
INCI: International Nomenclature of Cosmetic Ingredients.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
GefStoffVO: Ordinance on Hazardous Substances, Germany.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
DNEL: Derived No Effect Level.
PNEC: Predicted No Effect Concentration.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION